

# ELEVATING POST TABLE

## HYDRAULIC POST TABLE

Built for fast and efficient lifting, transporting and positioning of equipment and materials. Long lasting hydraulic pump is foot operated providing flexibility and portability.

**Model HT-03-1618**  
*Single-Post Lift Table*



**Model HT-10-2036**  
*Two-Post Lift Table*



**Model HT-30-3036**  
*Four-Post Lift Table*



- Foot pedal hydraulic pump operation
- All steel construction with welding to meet the A.W.S.
- Two rigid and two swivel polyurethane casters
- Floor brake to secure table to floor
- Push handle
- Unit is painted safety yellow
- Battery operated power option is available

MODEL NO.	CAPACITY (lbs.)	STANDARD LIFT RANGE	LOW PROFILE LIFT RANGE	SHORT PUMP LIFT RANGE	PLATFORM SIZE (W x L)	CASTER SIZE	WEIGHT (lbs.)
HT-03-1618	300	31" - 49"	n/a	28" - 43"	16" x 18"	4" x 2"	125
HT-10-2036	1,000	36" - 54"	26" - 44"	33" - 48"	20" x 36"	5" x 2"	300
HT-20-2436	2,000	36" - 54"	26" - 44"	33" - 48"	24" x 36"	5" x 2"	375
HT-20-3036	2,000	36" - 54"	26" - 44"	33" - 48"	30" x 36"	5" x 2"	390
HT-20-3042	2,000	36" - 54"	26" - 44"	33" - 48"	30" x 42"	5" x 2"	420
HT-30-2436	3,000	36" - 54"	26" - 44"	33" - 48"	24" x 36"	5" x 2"	380
HT-30-3036	3,000	36" - 54"	26" - 44"	33" - 48"	30" x 36"	5" x 2"	395
HT-30-3042	3,000	36" - 54"	26" - 44"	33" - 48"	30" x 42"	5" x 2"	425
HT-LP	Low profile option (not available on HT-03-1618)						
HT-SP	Short pump option						
HT-DC	Battery power option (not available on HT-03-1618)						

## POST LIFT AND TILT TABLE

- Two rigid and two swivel polyurethane casters
- Table is easily raised or lowered with a manual hydraulic foot pump
- Tilting top is actuated with manual hydraulic foot pump. Raise table to desired height then lock legs. Unlock top and continue operating foot pump to tilt table.
- Table tilting range varies from 0° to 30°
- Foot operated floor lock
- Support lip is 3" high
- Push handle
- Unit is painted safety yellow



- Position work materials quickly & easily
- Reduce fatigue and overexertion
- Decrease cumulative trauma injuries
- Increase productivity

MODEL NO.	CAPACITY (lbs.)	PLATFORM SIZE (W x L)	LIFT RANGE	CASTER SIZE	WEIGHT (lbs.)
PL/T-10-2036	1,000	20" x 36"	36" - 54"	5" x 2"	350
PL/T-20-2436	2,000	24" x 36"	36" - 54"	5" x 2"	385
PL/T-20-3036	2,000	30" x 36"	36" - 54"	5" x 2"	465
PL/T-20-3042	2,000	30" x 42"	36" - 54"	5" x 2"	525
PL/T-30-2436	3,000	24" x 36"	36" - 54"	5" x 2"	400
PL/T-30-3036	3,000	30" x 36"	36" - 54"	5" x 2"	505
PL/T-30-3042	3,000	30" x 42"	36" - 54"	5" x 2"	530

## MECHANICAL POST TABLE

MT-2436-LP



Sprocket/gear mechanism holds table at a fixed height without downward drift. Two-speed gear operation allows heavy loads to move at a low speed of 1/8" per crank rotation and light loads to move at high speed of 3/4" per crank rotation. 5" x 2" polyurethane casters and a foot operated floor lock are standard. Painted safety yellow.

MODEL NO.	CAPACITY (lbs.)	LIFT RANGE	PLATFORM SIZE (W x L)	WEIGHT (lbs.)
<b>LOW PROFILE</b>				
MT-2436-LP	2,000	24" - 42"	24" x 36"	350
MT-2442-LP	2,000	24" - 42"	24" x 42"	380
MT-3042-LP	2,000	24" - 42"	30" x 42"	430
MT-3048-LP	2,000	24" - 42"	30" x 48"	470
<b>HIGH PROFILE</b>				
MT-2436-HP	2,000	28" - 46"	24" x 36"	370
MT-2442-HP	2,000	28" - 46"	24" x 42"	400
MT-3042-HP	2,000	28" - 46"	30" x 42"	450
MT-3048-HP	2,000	28" - 46"	30" x 48"	490



**Vestil Manufacturing Company**

P.O. Box 570

Angola, IN 46703

Ph.: (219)665-7586

Fax: (219)665-1339

E-mail: vestil@dmci.net Web: www.vestilmfg.com

**Distributed by:**