

# FLOOR LOCKS



**APPLICATIONS** • Platform Trucks • Dollies • Carts • All Castered Equipment

## Side Mounted Floor Lock




### Model - FL-LK-SMR

- Automatically locks when operator pushes pedal.
- Spring loaded pad accommodates uneven floors.
- Mounts with pad 1-1/2 inches off floor.

#### SPECIFICATIONS

- Mounting Height - 10" to 15-1/2"
- Retracted Height - 14-7/8"
- Weight - 8 lbs.
- Height - Up: 14-7/8" - Down: 16-7/8"



#### FLOOR LOCKS TOP PLATE SPECIFICATIONS

- Bolt Hole Spacing - 3" x 4"
- Mounting Bolt Size - 3/8"
- Overall Plate Size - 4-1/2" x 6-1/2"
- Thickness of Plate - 3/16"

## LEVELIZING JACKS

*For Raising, Leveling, and Stabilizing Portable Equipment.*



Retractable  
8" Crank

Fabric Reinforced  
Rubber Pad

Our Zinc Plated Levelizing Jacks have a divided housing with flange plates for bolting above and below frame of equipment. Units have a capacity of 5,000 lbs.

Three rotations yield one inch stroke

Model Number	Overall Height	Min. Ht. Below Frame of Equip.	Max. Extended Ht. Below Frame of Equip.	Length of Screw Travel	Weight (lbs.)
LJ-9	18"	4 1/2"	13 1/2"	9"	11 lbs.
LJ-17	26"	4 1/2"	21 1/2"	17"	13 lbs.

# Retractable Floor Lock

*Provides 3-1/4" Ground Clearance*

## Model - FL-LK-S

### SPECIFICATIONS

- Mounting Height - 7-3/8"
- Retracted Height - 4-3/8"
- Used w/Caster Size - 6"
- Capacity - 1,000 lbs.
- Weight - 10 lbs.

### FLOOR LOCK TOP PLATE SPECIFICATIONS

- Bolt Hole Spacing - 2-7/16" x 4-15/16"
- Mounting Bolt Size - 1/2"
- Overall Plate Size - 3-3/8" x 6-1/4"
- Thickness of Plate - 7/16"



**Aluminum Enamel Finish**

# Ductile Iron Floor Lock

- Push down pedal for automatic locking
- Lift with toe to unlock
- Approximately one inch ground clearance



**Model - FL-LK-5X**



**Aluminum Enamel Finish**

### Specifications

Model Number	Mounting Height	Retracted Height	Used w/Caster Size	Capacity	Weight
FL-LK-5G	5-5/8"	4-11/16"	4"	1,000 lbs.	8 lbs.
FL-LK-5X	5-1/32"	4-11/16"	4"	1,000 lbs.	8 lbs.
FL-LK-7X	7-1/4"	6-1/4"	6"	1,000 lbs.	10 lbs.
FL-LK-7G	7-3/4"	6-3/4"	6"	1,000 lbs.	10 lbs.
FL-LK-10	9-15/16"	8-7/8"	8"	1,000 lbs.	16 lbs.

### Floor Lock Top Plate Specifications

Model Number	Bolt Hole Spacing	Mounting Bolt Size	Overall Plate Size	Thickness of Plate
FL-LK-5G	2-5/8" x 3-5/8"	3/8"	3-11/16" x 5-8"	3/8"
FL-LK-5X	2-5/8" x 3-5/8"	3/8"	3-11/16" x 5-8"	3/8"
FL-LK-7X	2-7/16" x 4-15/16"	1/2"	4-1/2" x 6"	7/16"
FL-LK-7G	2-7/16" x 4-15/16"	1/2"	4-1/2" x 6"	7/16"
FL-LK-10	3-3/8" x 5-1/4"	1/2"	5-3/8" x 7-1/4"	3/8"



**Vestil Manufacturing Company**

P.O. Box 570  
 Angola, IN 46703  
 Ph.: (219)665-7586 Fax: (219)665-1339  
 E-mail: vestil@dmci.net Web: www.vestilmfg.com

**Distributed by:**